RUNPO 5 - Profi -cable pulling system optimal for pipe diameters 16 mm - 40 mm

Item no.: 10013 | 10014





DATA		
ITEM NO.	10013	10014
LENGTH	20 m	30 m
TOTAL WEIGHT	1,06 kg	1,30 kg
DIMENSIONS	H 45 / B 315 / T 395	
MATERIAL	triple twisted special plastic tape	
Ø ROD	5,3 mm	
BENDING RADIUS	15 mm	
TOTAL BREAKING LOAD	270 kg	
TUBE DIAMETER	for pipe dimensions 16 mm - 40 mm	
EAN-Code	9120045472806	9120045472813

DESCRIPTION

The RUNPO5 is another innovation by RUNPOTEC and a genuine "all-rounder". The patented viewfinder tip, the RUNPOGLEITER with twist compensation allows even the tightest radii to be overcome, with a total breaking load of an incredible 270 kg in relation to the entire pulling system. The special plastic strap with a diameter of 5.3 mm and a triple twist has an even better shearing effect than the 3 mm glass fibre rod; the frictional resistance is only half the normal value due to spot contact. Labour- and time-consuming repair work is no longer necessary, as this cable pulling system is virtually breakage-free. The RUNPO5 can be stowed in a very practical box in lengths of 20 m and 30 m. The 40 m RUNPO5 strap cannot be stored in the box.

Optimal field of application: for pipe dimensions 16 mm - 40 mm

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.runpotec.com.

Scope of delivery: RUNPO5 in plastic box - all RUNPO 5s are delivered from the factory with $2\,x$ RUNPOGLEITER with twist compensation at the beginning and end of the spiral.

ADVANTAGES

- √ 50% less frictional resistance
- √ 270 kg Total breaking load
- ✓ Virtually break-free even with the tightest radii
- Advantages compared to glass fibre rod no buckling, sticking => time savings
- Guide tip (RUNPOGLEITER) with integrated twist compensation
- 2 RUNPOGLEITER with twist compensation at the start and end of the spiral

